

W. 86th St. 8600 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER 23 TOWNSHIP _ 4-23-2000 F: Wilcoxen <u> 17</u> RANGE _ 6700 PARTY CHIEF: -CREW: _ TYPE OF MARKER: Harrison 465 8-16-95 Section METHOD OF ESTABLISHMENT: County: IN. S.P.C. E ZONE, NAD 83 NAME: 17022305 N: 516945.2333(m) E: 48467.5683(m) THIS CORNER POSITION REPRESENTS A "TITLE" CORNER
AND MAY NOT NECESSARILY
REPRESENT THE POSITION
BASED ON RECORD CORNERS THIS CORNER POSITION RE-7. 6. pavement 1-465 00 59.60 2. 55.5'+/-Line of 82nd St. 8200 N 5. Edge_of ⁷6.95, 119.44 Section Line 6150 3. 4.

Hosbrook 8-5-1851 called no stone, but witnesses: 24" oak N 9 W 25 links, 34' oak S 13 E 50 links per Pike Township Legal Survey Book pg. 19. Schmidt 9-1-61 called 4" square cut stone. Hankins 1-27-64 called the same. Miller 4-14-75 called 1/2" rebar. Wilcoxen 8-2-88 called the same. Excavated by Kiste 8-15-95 and a 1/2" rebar found at surface. Harrison set. Re-tied 4-23-2000 by Wilcoxen.

1	1	C	1	2	2	5	0	5	

REF.	DISTANCE	DESCRIPTION
1.	28.04	Center round steel fence post
2.	9'+/-	Due E to C/L of fence line
3.	119.44	NE I-beam sign support (E)
4.	76.95	NE I-beam sign support (W)
5.	55.5'+	_ Due W to edge of pavement I—465 N—bound
6.	59.60'	SE-bolt of E-sign support for 86th St. Exit #23
7.	56.21'	SE-bolt of E-sign support for 86th St. Exit #23